

SAFETY CAGE AK2



Application:

The Hauer safety cage provides a safe workplace in compliance with safety regulations governing municipal and similar applications. The safety cage with roof frame is TÜV-approved but users must have the complete combination of vehicle and safety cage retested by an accredited test institute for final approval as required by local regulations.

Using the safety cage on a Hauer front loader requires the installation of a safety package that comprises a tap in the tipping line and a drop rate control valve in the lifting line where it restricts maximum lift and drop rates to 0.4m/s. The safety package is available from Hauer. It is not permitted to operate the cage without the prior installation of this safety package on the front loader.

Description:

The Hauer AK2 safety cage is manufactured to a modular design. The base unit consists of a cage complete with handrail and mesh back. This level of specification can be extended by the following options: a roof frame with mesh back and mount for attachment to the stacker, an underframe that increases the work height by 1200 mm, roof including attachments for protection from falling objects, a toolbox and handrail lining for logging applications. The extremely resistant 2K two-stage paint coat offers superb protection from corrosion and can be refinished in the course of a long service life.

Width mm	Depth mm	Height mm	Base unit weight kg
1280	800	1250 / 2150 (with roof frame)	144



INNOVATION WITH TRADITION FOR LIFE.

Advantages:

- Low dead weight
- Modular design
- High payload (up to 250kg)

Standard specification:

- Base unit incl. handrail and SWE-EURO mount or Hauer mount
- Base specification cage complete with handrail and stacker mount
- Mesh back
- Attachments for safety belts
- Water level for cage levelling
- Sturdy stands
- Right-hand door
- Standard Hauer orange or Hauer matt black paint finish

Options:

- 1200 mm high underframe
- Roof frame with mesh back and stacker mount
- Roof incl. attachments
- Handrail lining for logging applications
- Toolbox
- Paint finish available in all RAL colours



Roof frame with mesh back



Stacker mountings



1200 mm high underframe



Handrail lining and toolbox

© Hauer 03/2019. Die gezeigten Bilder können vom serienmäßigen Lieferumfang abweichen. Irrtümer und technische Änderungen vorbehalten.